



| ITEM 項目 | PARTS NAME 零件名稱 | Q'TY 數量 | MATERIAL 材質 | FINISH/REMARK 處理/備註 |
|------------|--------------------|------------|-----------------|------------------------|
| 1 | TOP COVER | 1 | A.B.S | (Black) |
| 2 | BOTTOM COVER | 1 | A.B.S | (Black) |
| 3 | HOUSING | 1 | P.B.T+G.F | UL-94V-0 (Black) |
| 4 | LATCH | 1 | STAINLESS | Non-plating |
| 5 | CONTACT | 10 | Phosphor Bronze | Gold flash selective |

P.C.BOARD (Thickness:1.0mm)

SPECIFICATION
MATERIAL
 See drawing
STANDARD DATA
 Rating current:1.0A
 Operating temperature: -30°C ~ +60°C
 Storage temperature: -40°C ~ +85°C
ELECTRICAL
 Insulator resistance: 1000M ohms Min. @ 250 VDC
 Withstanding voltage: 100 VAC / minute
 Contact resistance: 130m ohms Max.
MECHANICAL
 Mating force: 30N(3.08kgf) Max.
 Unmating force (Without lock): 4.2N(0.43kgf) Min.
 Durability: 10000 cycles Min.
 Contact retention force: 4.2N(0.43kgf) Min

PART NO. A 0 1 - 556 - 10 D1

SERIES A=Plug In
 TYPE O=STANDARD TYPE
 CONTACT TYPE 1=Solder type

MODEL NO. 01=Type 1
 CONTACT NUMBER 10=10 position

CYPRESS INDUSTRIES
 www.cypressindustries.com

| | | | | | | | | | | | | | | | |
|---------|--------------|---------|----------------|---------|---------|---|------------|-------------|--|---------------|-----------------|---------------|-------------------------------|------------------------------|--------------|
| REV. 版本 | ECH NO. 取替號碼 | MARK 記號 | REVISIONS 變更內容 | SIGN 簽名 | DATE 日期 | UNLESS OTHERWISE SPECIFIED TOLERANCE 尺寸公差 X. ±0.50 .X ±0.30 .XX ±0.20 ANG. ±5°00' | CHECKED 審核 | DESIGNED 設計 | TITLE 產品名稱 PLUG IN for Palm 3,7,M100 Solder type-10 position | UNIT 單位 MM | SCALE 比例 5/2 | SIZE 尺寸 A3 | PART NO. 產品料號 A01-556-1001 | DOC. NO. 文件編號 CUT-556-001 | REV. 版本 A |
| A | EXXXX-XXX | △ X 0 | - | - | - | | | | | | | | | | |